

Flex-Flash FH-16

GENERAL DESCRIPTION

Flex-Flash FH-16 – Polyester SB nonwoven reinforcing fabric.

BASIC USE

For use with Hydrotech Monolithic Membrane 6125[®] as a horizontal reinforcement on :

- Precast and cast-in-place concrete decks.
- Gypsum and plywood decks.



FORM

Available in rolls of :

Width	Length	Rolls per package
150 mm (6 in.)	182.8 m (200 yards)	5
300 mm (12 in.)	182.8 m (200 yards)	3
1000 mm (39 in.)	182.8 m (200 yards)	1

PHYSICAL PROPERTIES

Properties	Test Method	Unit		Target
Weight	ASTM D-3776	Oz/sq. yard		1.4
Thickness	ASTM D-1777	Mils		10.4
MD			MD	32
Tensile Strength	ASTM D5035-90	Pound/in.		
CD			CD	25
MD			MD	7
Tear Strength	ASTM D-5733-99	Pound		
CD			CD	9

LEED INFORMATION

	Credit 4	Credit 5
Recycled Content (% by weight)	0	
Manufacture Location		Tennessee, U.S.A.
Extraction/Harvesting Location		N/A
VOC Content (g/L)		

The contents and methods described herein are the intellectual property of Hydrotech Membrane Corp.. The information is based on data and knowledge considered to be true and correct at the time of publication and is offered for the user's consideration, investigation and verification. The information is subject to change without notice. The determination of suitability and fitness of the products and the application described herein for a particular purpose are the sole responsibility of the user. Please read all statements, recommendations and suggestions in conjunction with the conditions of sale which apply to all goods sold by Hydrotech Membrane Corp., including the express disclaimers by each company of the implied warranties of merchantability or fitness for a particular purpose.